

# ADM-16DX VIDEO MULTIPLEXER

## WITH IR REMOTE CONTROL



### FEATURES

- 16 Camera PAL/NTSC dual system Color inputs / Full Looping out.
- Infrared Remote Control for easy Operation.
- Easy on screen Menu for user program selection.
- S-VHS Output/Input for VCR.
- High Definition Digital Color Processing.
- Multi-Direction Motion Detection & Activity Detection.
- Custom Alarming setup.
- Programmable sequential time setting.
- Full screen, Freeze, PIP, 4 Picture, 9 Picture, 13 Picture, 16 Picture Display.
- 2X2 Digital Zoom display.
- 150 Alarm List.
- Upgradeable to Remote Transmission.
- Optional)

### SPECIFICATION:

Video Signal NTSC/EIA & PAL/CCIR  
Video Format NTSC/EIA: 525 Lines, 60 Fields per sec.  
PAL/CCIR: 625 Lines, 50 Fields per sec.  
Resolution 720X480 NTSC  
768X512 PAL  
Video Input BNC, 1 Per Camera.  
Video Output BNC, 1 Looping out Per Camera.  
Monitor Output BNC, 1 main monitor & 1 call monitor.  
VCR In/Out BNC: 1 In & 1 Out /S-VHS: 1 In & 1 Out.  
Alarm Input 16 Dry Contact Input, +5 to +12 V DC or TTL/CMOS Signal.  
DB-25 Female connector.  
Alarm Output 1 NO output & 1 NC output at DB-25 Female connector.  
Alarm Log List 150 Alarm sets.  
Motion Detection 16 X 12 total 192 Grid & 1 to 100 motion sensitivity adjustable.  
Remote Control Full function Infrared Remote control.  
Power 85 to 270 VAC/ 50-60Hz.  
Dimensions 44 mm(H) X 432 mm(W) X 350 mm(D)  
Weight 4.4 lbs. (2.0 kg.)  
Operating Temp 32F-104F (0C-40C)

